

STACO ENERGY PRODUCTS CO. MP SERIES MICROPROCESSOR CONTROLLER PROVIDES FOR EASY INTERFACE OF COMPUTER AND PROCESS CONTROL TO STACO'S MOTOR DRIVEN VARIABLE TRANSFORMERS. AVAILABLE OPTIONS INCLUDE BI-DIECTIONAL RS232/RS422/IEEE488 COMMUNICATION PORTS, ONE TO THREE CHANNEL OPTIONS FOR UP TO THREE PHASE APPLICATIONS, PROCESS CONTROL SETPOINT, ISOLATION OF FEEDBACK OR SETPOINT SIGNALS, AND RMS/AVERAGE/PEAK SENSING. FOR LOCAL CONTROL AND MONITORING APPLICATIONS, A PANEL OR REMOTE MOUNTED MICROTERMINAL IS AVAILABLE.

UNLESS OTHERWISE SPECIFIED. TOLERANCE IS ± DECIMALS HOLES ANGLES DRAFT .XX ±0±0.06 .002 1° 1-1/2° .XXX .005	UNITS IN [mm]	SPEC. CONTROL DRAWING						
MATERIAL : ALL DIMENSIONS		MICROPROCESSOR				ENERGY PRODUCTS CO.		
	APPLY AFTER PLATING	CONTROLLER				DAYTON, OHIO U.S.A.		
The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sale rights thereto, and to any orticle disclosed therein except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts.		DRAWN BY S.A. SMITH	5/22/92	FIRST USED ON MPAT	DO NOT SCALE DWG.	CUSTOMER APPROVAL		DATE
		CHECKER	DATE	WEIGHT APPROX. 18 LBS	CODE IDENT. NO. 83008	DWG. DWG. NO. SIZE		
		ENGINEER	DATE	SCALE 1=1	SHEET 1 OF 2	D	095-0)535

095-0535